

**MSDS**Definition  
of terms**Material Safety Data Sheet for #2 Diesel****1. Chemical Product****MSDS Number:** U7770**MSDS Date:** 01-31-99**Product Name:** #2 Diesel Fuel

**24 Hour Emergency Phone: (210) 979-8346**  
**Transportation Emergencies: Call Chemtrec at 1-800-424-9300**  
 MSDS Assistance: (210) 592-4593

**Distributors Name and Address:**

T.W. Brown Oil Co., Inc.  
 1857 Knoll Drive  
 Ventura, California 93003

**Chemical Name:** #2 Diesel Fuel**Cas Number:** 68476-34-6

**Synonyms/Common Names:** This Material Safety Data Sheet applies to the following product descriptions for Hazard Communication purposes only. Technical specifications vary greatly depending on the product, and are not reflected in this document. Consult specification sheets for technical information.

**California Air Resources Board (Carb) Diesel Fuel-** On-road, Off-Road, Tax Exempt blends

**Premium Diesel Fuel-** Low-Sulfur, High-sulfur, On-Road, Off-Road, Tax Exempt blends

**#2 Distillate-** Low-Sulfur, High-sulfur, On-Road, Off-Road, Tax Exempt blends

**#2 Diesel Fuel-** Low-Sulfur, High-sulfur, On-Road, Off-Road, Tax Exempt blends

**#2 Fuel Oil-** Low-Sulfur, High-sulfur, On-Road, Off-Road, Tax Exempt blends

**2. Composition, Information On Ingredients**

**Product Use:** This product is intended for use as a fuel in engines and heaters designed for diesel fuels, and for use in engineered processes. Use in other applications may result in higher exposures and require additional controls, such as local exhaust ventilation and personal protective equipment.

**Description:** #2 Diesel is a complex mixture of hydrocarbons from a variety of chemical processes blended to meet standardized product specifications. Composition varies greatly and includes C9 to C20 hydrocarbons with a boiling range of about 325-675 degrees F. The following is a non-exhaustive list of common components, typical percentage ranges in product, and occupational exposure limits for each.

Component or Material Name	%	CAS Number	ACGIH Limits TLV -- STEL -- Units	OSHA Exposure Limits PEL -- STEL -- C/P -- Units
Cat cracked distillate, light	0-100	64741-59-9	100 -- NA -- mg/m3	N/A -- N/A -- N/A -- N/A
Hydrotreated distillate, middle	0-100	64742-46-7	100 -- NA -- mg/m3	N/A -- N/A -- N/A -- N/A

Hydrotreated distillate, light	0-100	64742-47-8	100 -- NA -- mg/m3	N/A -- N/A -- N/A -- N/A
Gas oil, light	0-100	64741-44-2	100 -- NA -- mg/m3	N/A -- N/A -- N/A -- N/A

### 3. Hazards Identification

#### Health Hazard Data:

1. The major effect of exposure to this product is giddiness, headache, central nervous system depression; possible irritation of eyes, nose, and lungs; and dermal irritation. Signs of kidney and liver damage may be delayed. Pulmonary irritation secondary to exhalation fo solvent.
2. NIOSH recommends that whole diesel engine exhaust be regarded as a potential occupational carcinogen. Follow OSHA and NSHA rules where diesel engine exhaust fumes may be generated.
3. A life time skin painting study by the American Petroleum Institute has shown that similar naphtha products with a boiling range of 350-700 degrees F usually produce skin tumors and/ or skin cancers in laboratory mice. Only a weak to moderate response occurred. The effect to humans has not been determined.
4. Positive results at 2.0 ml/kg and 6.0 ml/kg noted in mutagenesis studies via in-vivo bone marrow cytogenetics assay in rats.
5. Kerosene is classified as a severe skin irritant. Mutation data has been reported for kerosene products. Hydrotreated kerosene is listed as being probably carcinogenic to humans with limited evidence in humans and sufficient evidence in experimental animals.

**Hazards of Combustion Products:** Carbon monoxide and carbon dioxide can be found in the combustion products of this product and other forms of hydrocarbon combustion. Carbon monoxide in moderate concentrations can cause symptoms of headache, nausea, vomiting, increased cardiac output, and confusion. Exposure to higher concentrations of carbon monoxide can cause loss of consciousness, heart damage, brain damage, and/or death. Exposure to high concentrations of carbon dioxide can cause simple asphyxiation by displacing available oxygen. Combustion of this and other similar materials should only be carried out in well ventilated areas.

< Home

Next >